

Baldwin Locomotive Works, South Euclid, Ohio

E S. ABOVE

THE BALDWIN LOCOMOTIVE WORKS

Specification Card for Locomotive No. **15**

~~Railway Valley owned by:~~ **MONADNOCK STEAM**
ONEIDA WESTERN ~~JOHN & NORTHERN~~

Owned by **ONEIDA WESTERN**
Operated by **ONEIDA WESTERN**

Railroad Company.

Railroad Company.

Builder, The Baldwin Locomotive Works.

Builder's No. of Boiler **43529**

When built **June 1916**

Where built **Philadelphia**

Type of boiler **Straight Top (radial stayed)**

Material of boiler shell sheets **Steel**

Material of rivets **Steel**

Dome, where located **On 2nd course**

Grate area in sq. ft. **29.5**

Height of lowest reading of gauge glass above crown sheet **35"**

Height of lowest gauge cock above crown sheet **35"**

Water-bar tubes, O. diam. **None** thickness **----**

Arch tubes, O. diam. **None** thickness **----**

Fire tubes, number **250**

" " O. diam. **2"** length **161"**

Safety valves:

No. Size Make Style

2 **3"** **Consolidated** **Oper.**

Firebox stay bolts, O. diam. **7/8"** spaced **4" x 4"**

Combustion chamber stay bolts, O. diam. **None**

" " " " spaced **---- x ----**

Crown stays, O. diam., top **1"** bottom **1"**

" " spaced **4" x 4"**

Crow-bar rivets, O. diam., top **None** bottom **None**


" " spaced **---- x ----**

Water space at firebox ring sides **3 1/2"**

back **3 1/2"** FRONT **3 1/2"**

Width of water space at sides of firebox measured at center **5"** back **6 1/4"**

Mak
indicating



rivets used in shell of border,
seams.

V

The maximum stresses at the allowed working pressure were found by calculation to be as follows:

Stay bolts at root of thread	6920	lbs. per sq. in.
Stay bolts at reduced section	7230	" " "
Crown stays XXXXXX at XXXXXX smallest section; top	5330	lbs. per sq. in.
Crown-bar rivets XXXXXX crown-bar rivets XXXXXX	None	lbs. per sq. in.
Round XXXXXX braces	8900	lbs. per sq. in.
Gusset braces	None	" " "
Shearing stress on rivets	7560	" " "
Tension on net section of plate in longitudinal seam of lowest efficiency, pounds per sq. in.	11400	

Dimensions and data taken from locomotive were furnished by -----

Data upon which above calculations were made were obtained from Drawing No. 11766 and 11767

Dated ---- furnished by The Baldwin Locomotive Works Company

Arnold A. Wright
Mechanical Engineer.

STATE OF **PENNSYLVANIA**
COUNTY OF **PHILADELPHIA** } SS:

Arnold A. Wright being duly sworn says that he is the officer who signed the foregoing specification, that he has satisfied himself of the correctness of the drawings and data used, and verified all of the calculations, and has examined the record of present condition of boiler dated -----

June 16, 1916 and sworn to by inspector L.F. Stang and H. Atlan
and believes that the design, construction, and condition of boiler No. 43539 renders it safe for a working pressure of 200 pounds per square inch.

Arnold A. Wright
(Name of affiant)

Subscribed and sworn to before me
this 5 day of July, 1916

Edgar S. Howard
My commission expires at the end of
the next session of the state senate.

Approved:

J. F. Ashworth

Approved:

Title

Date

Approved *Carl C. Core*
Title Asst. Chief Mech. Officer

Date B&MRR July 16, 1962

The Boston & Maine Railroad
approved for Monadnock,
Steamtown & Northern Corp.
F. Nelson Blount President.

Approved:

Title

Date

Place

Signature

Date

</